

REFRESH

DUALTREAT® REFRESH is a high-quality maintenance solution for concrete surfaces. It has been especially designed for areas with high people and machinery traffic. DUALTREAT REFRESH refreshes concrete floors that have been treated previously with a DUALTREAT® system.

RECOMMENDED FOR: All concrete surfaces.

RECOMMENDATION: Always make a test coat to ensure the compatibility of product and surface.

PREPARATION: Ensure the surface is clean and dry.

APPLICATION: Use a low-pressure pump and distribute DUALTREAT® REFRESH with a mop evenly and saturated on the surface. Avoid sagging and puddles and keep the surface wet for a minimum of 10 minutes – re-apply if necessary on non-saturated areas. Only one coat is required. A minimum temperature of 5°C is required for the application.

COVERAGE RATE: 75-100 ml per m² depending on surface porosity and density.

REMARK: It is necessary to apply as much product as to keep the surface wet for 10 minutes without any sagging or puddles.

DRYING TIME: 30–60 minutes under average weather conditions (depending on substrate and temperature).

APPEARANCE. Transparent liquid.

PACKAGING: 25 litres can (24 cans/pallet).

EQUIPMENT CARE: The equipment has to be cleaned up in water directly after use.

STORAGE: Store away from direct sunlight, sources of heat and protected from frost.

SHELF LIFE: 24 months (in original sealed can).

SAFETY AND REGULATIONS: DUALTREAT® REFRESH is not classified as hazardous according to current labelling. It is harmful if swallowed and repeated exposure may cause skin dryness or cracking. For detailed information regarding handling precautions please consult the safety data sheet and the product label.

FEATURES AND BENEFITS:

- ❖ Maintains sustainably concrete floors that have been treated previously with a DUALTREAT® system.
- ❖ Especially designed for areas with high people and machinery traffic.
- ❖ Improves the functionality, appearance and look of concrete surfaces.
- ❖ UV-stable and will not yellow or change the original look of the surface.
- ❖ No VOC content, low odour.
- ❖ Environmentally friendly.
- ❖ Easy and quick application.
- ❖ Transparent.
- ❖ May be used at lower temperatures.
- ❖ For use inside and outside.

We recommend to use on treated surfaces cleaning agents with a PH-value between of 7-9.

The information contained in this documentation has been compiled in accordance with the latest technology, experience and knowledge. In view of the variety of individual projects that exist, the buyer and/or user is not released from his obligation to examine our materials to its own responsibility for the suitability for the intended use. A new datasheet replaces the information contained herein.

Last updated – January 2015